Safety Data Sheet

Revision Date 10-Oct-2020 Version 14 Supercedes Date: 20-Mar-2019

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product Identifier

Product code AC200MS

Product name Medium Solids Clearcoat

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Paint, Coatings

1.3. Details of the supplier of the safety data sheet

See section 16 for more information

Valspar Corporation Level 4, 2 Burbank Place Baulkham Hills, New South Wales 2153

Valspar Corporation 2-14 Patiki Road, Avondale 1026 Auckland, New Zealand

For further information, please contact

E-mail address sdshelpdesk@valspareurope.com

1.4. Emergency telephone number

Australia +(61)-290372994 **New Zealand** +(64)-98010034

Poison control centre phone

number

Australia 13 11 26

New Zealand 0800 764-766

Section 2: HAZARDS IDENTIFICATION

GHS - Classification

Aspiration toxicity	Category 1
Skin Corrosion/Irritation	Category 3
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Acute aquatic toxicity	Category 3
Chronic Aquatic Toxicity	Category 3
Flammable liquids	Category 2

Label elements



Signal word

DANGER

Contains Solvent naphtha, petroleum, light aromatic, Benzene, trimethyl-, Xylenes (o-, m-, p- isomers), 1,3,5-Trimethylbenzene , n-Butyl acetate, Acetone, 1,2,4-Trimethylbenzene

HAZARD STATEMENTS

Highly flammable liquid and vapour
Causes mild skin irritation
Causes serious eye irritation
May cause drowsiness or dizziness
Harmful to aquatic life with long lasting effects
May be fatal if swallowed and enters airways
AUH066 - Repeated exposure may cause skin dryness or cracking

PREVENTION

Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection

Avoid breathing dust/fume/gas/mist/vapours/spray

Use only outdoors or in a well-ventilated area

Avoid release to the environment

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wear protective gloves/protective clothing/eye protection/face protection

Keep cool

RESPONSE

Get medical advice/attention if you feel unwell

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Skin

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

INHALATION

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

INGESTION

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

FIRE

In case of fire: Use CO2, dry chemical, or foam for extinction

STORAGE

Store locked up

Store in a well-ventilated place. Keep container tightly closed

DISPOSAL

Dispose of contents/container to an approved waste disposal plant

OTHER HAZARDS

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
n-Butyl acetate	123-86-4	25 - 50
Acetone	67-64-1	10 - 25
Solvent naphtha, petroleum, light aromatic	64742-95-6	5 - 10
Methyl n-amyl ketone	110-43-0	3 - 5
Benzene, trimethyl-	25551-13-7	3 - 5
Xylenes (o-, m-, p- isomers)	1330-20-7	1 - 3
1,3,5-Trimethylbenzene	108-67-8	1 - 3
1,2,4-Trimethylbenzene	95-63-6	1 - 3
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimeth ylethyl)-4-hydroxyphenyl]-1-oxopropyl]omegah ydroxy-	104810-48-2	0.1 - 0.3
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.1 - 0.3

If this section is blank, there are no hazardous components per NOHSC guidelines.

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice

IF exposed or concerned: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin contact

If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

INHALATION

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

INGESTION

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsTreat symptomatically.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitisation by skin contact.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

HAZCHEM Code: 3YE

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Avoid breathing vapours or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Methods for Containment

Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General hygiene considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorised personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical name	Australia	New Zealand	ACGIH TLV
n-Butyl acetate	TWA: 150 ppm	TWA: 150 ppm	STEL: 150 ppm
123-86-4	TWA: 713 mg/m ³	TWA: 713 mg/m ³	TWA: 50 ppm
	STEL: 200 ppm	STEL: 200 ppm	
	STEL: 950 mg/m ³	STEL: 950 mg/m ³	
Acetone	TWA: 500 ppm	TWA: 500 ppm	STEL: 500 ppm
67-64-1	TWA: 1185 mg/m ³	TWA: 1185 mg/m ³	TWA: 250 ppm
	STEL: 1000 ppm	STEL: 1000 ppm	
	STEL: 2375 mg/m ³	STEL: 2375 mg/m ³	
Methyl n-amyl ketone	TWA: 50 ppm	TWA: 50 ppm	TWA: 50 ppm
110-43-0	TWA: 233 mg/m ³	TWA: 233 mg/m ³	
Benzene, trimethyl-	TWA: 25 ppm	TWA: 25 ppm	TWA: 25 ppm
25551-13-7	TWA: 123 mg/m ³	TWA: 123 mg/m ³	
Xylenes (o-, m-, p- isomers)	TWA: 80 ppm	TWA: 50 ppm	STEL: 150 ppm
1330-20-7	TWA: 350 mg/m ³	TWA: 217 mg/m ³	TWA: 100 ppm
	STEL: 150 ppm		
	STEL: 655 mg/m ³		
1,3,5-Trimethylbenzene	TWA: 25 ppm	TWA: 25 ppm	TWA: 25 ppm
108-67-8	TWA: 123 mg/m ³	TWA: 123 mg/m ³	
1,2,4-Trimethylbenzene	TWA: 25 ppm	TWA: 25 ppm	TWA: 25 ppm
95-63-6	TWA: 123 mg/m ³	TWA: 123 mg/m ³	

Biological Limit Values:.

Chemical name	Australia	New Zealand
Acetone 67-64-1		50 mg/L urine end of shift Acetone
Xylenes (o-, m-, p- isomers) 1330-20-7		1.5 g/L urine end of shift Methylhippuric acid

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Personal Protective Equipment

Eye/Face Protection

Tight sealing safety goggles.

Skin and Body Protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre.

Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water Local authorities should be advised if significant spillages cannot be contained

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance No information available

Odour Solvent Colour Clear

Odour threshold
PH
No information available
Soiling point / boiling range
Flash Point
No information available
56.05 °C / 133 °F
-20 °C / -4 °F

Method

Evaporation Rate No information available Flammability (solid, gas) No information available

Flammability limit in air

Upper flammability limit:
Lower flammability limit
Vapour pressure
Vapour Density

No information available
No information available
No information available

Specific gravity .94

Solubility(ies) No information available **Partition coefficient** No information available **Autoignition Temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity No information available Dynamic viscosity **Explosive Properties** No information available **Oxidising Properties** No information available

9.2. Other information

Molecular Weight No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

No information available.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerisation

None under normal processing.

Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

Strong oxidising agents.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide (CO2). Chlorine gas.

Section 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Information on Likely Routes of Exposure

Eye Contact Skin contactCauses serious eye irritation.

Causes mild skin irritation.

INGESTION May be fatal if swallowed and enters airways.

INHALATION May cause drowsiness or dizziness.

Numerical Measures of Toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 13,248.00 Mg/kg ATEmix (dermal) 47,606.00 Mg/kg ATEmix (inhalation-dust/mist) 14.50 Mg/l ATEmix (inhalation-vapour) 106.00 Mg/l

UNKNOWN ACUTE TOXICITY .0001% of the mixture consists of ingredient(s) of unknown toxicity.

Numerical Measures of Toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	= 3400 ppm (Rat) 4 h
Methyl n-amyl ketone 110-43-0	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12600 μL/kg(Rabbit)= 12.6 mL/kg(Rabbit)	2000 - 4000 ppm (Rat) 6 h
Benzene, trimethyl- 25551-13-7	= 8970 mg/kg (Rat)	-	-
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit)> 4350 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 29.08 mg/L (Rat) 4 h
1,3,5-Trimethylbenzene 108-67-8	= 5000 mg/kg (Rat)	-	= 24 g/m³(Rat)4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³(Rat) 4 h
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-benzotriazol-2-yl)- 5-(1,1-dimethylethyl)-4-hydroxyphen yl]-1-oxopropyl]omegahydroxy- 104810-48-2	-	-	-
Bis(1,2,2,6,6-pentamethyl-4-piperidy I) sebacate 41556-26-7	= 2615 mg/kg(Rat)	<u>-</u>	<u>-</u>

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin Corrosion/IrritationCauses mild skin irritationSerious eye damage/eye irritationCauses serious eye irritation

Skin SensitisationNot applicableRespiratory SensitisationNot applicableGerm Cell MutagenicityNot applicableCarcinogenicityNot applicableReproductive toxicityNot applicable

Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Xylenes (o- m- p- isomers)

Xylenes (o-, m-, p- isomers) Kidney, Liver, Nervous System May cause drowsiness or dizziness Not applicable

Aspiration Hazard

May be fatal if swallowed and enters airways

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity Harmful to aquatic life with long lasting effects

Environmental Precautions Prevent product from entering drains.

Chemical name	Algae/aquatic plants	Fish	Crustacea
n-Butyl acetate 123-86-4	= 674.7 mg/L Desmodesmus subspicatus 72 h EC50	= 62 mg/L Leuciscus idus 96h LC50 17 - 19 mg/L Pimephales promelas 96h LC50 = 100 mg/L Lepomis macrochirus 96h LC50	= 72.8 mg/L Daphnia magna 24h EC50
Acetone 67-64-1		4.74 - 6.33 mL/L Oncorhynchus mykiss 96h LC50 6210 - 8120 mg/L Pimephales promelas 96h LC50 = 8300 mg/L Lepomis macrochirus 96h LC50	12600 - 12700 mg/L Daphnia magna 48h EC50 10294 - 17704 mg/L Daphnia magna 48h EC50
Solvent naphtha, petroleum, light aromatic 64742-95-6		= 9.22 mg/L Oncorhynchus mykiss 96h LC50	= 6.14 mg/L Daphnia magna 48h EC50
Methyl n-amyl ketone 110-43-0		126 - 137 mg/L Pimephales promelas 96h LC50	
Benzene, trimethyl- 25551-13-7		= 7.72 mg/L Pimephales promelas 96h LC50	
Xylenes (o-, m-, p- isomers) 1330-20-7		> 780 mg/L Cyprinus carpio 96h LC50 = 780 mg/L Cyprinus carpio 96h LC50 23.53 - 29.97 mg/L Pimephales promelas 96h LC50 7.711 - 9.591 mg/L Lepomis macrochirus 96h LC50 = 19 mg/L Lepomis macrochirus 96h LC50 13.1 - 16.5 mg/L Lepomis macrochirus 96h LC50 13.5 - 17.3 mg/L Oncorhynchus mykiss 96h LC50 2.661 - 4.093 mg/L Oncorhynchus mykiss 96h LC50 = 13.4 mg/L Pimephales promelas 96h LC50 30.26 - 40.75 mg/L Poecilia reticulata 96h LC50	= 3.82 mg/L water flea 48h EC50 = 0.6 mg/L Gammarus lacustris 48h LC50
1,3,5-Trimethylbenzene 108-67-8		= 3.48 mg/L Pimephales promelas 96h LC50 = 7.72 mg/L Pimephales promelas 96h LC50	= 50 mg/L Daphnia magna 24h EC50
1,2,4-Trimethylbenzene 95-63-6		= 7.72 mg/L Pimephales promelas 96h LC50 7.19 - 8.28 mg/L Pimephales promelas 96h LC50	= 6.14 mg/L Daphnia magna 48h EC50
Bis(1,2,2,6,6-pentamethyl-4-piperidy I) sebacate 41556-26-7		= 0.97 mg/L Lepomis macrochirus 96h LC50	= 20 mg/L Daphnia magna 24h EC50

Persistence and Degradability No information available. Bioaccumulation No information available.

No information available. **Mobility**

Chemical name	Partition Coefficient (n-octanol/water)
n-Butyl acetate 123-86-4	1.81
Acetone 67-64-1	-0.24
Methyl n-amyl ketone 110-43-0	1.98
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15
1,2,4-Trimethylbenzene 95-63-6	3.63
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	0.37

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused **Products**

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging

Improper disposal or reuse of this container may be dangerous and illegal. Empty

containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

14.1 UN/ID no 14.2 Proper Shipping Name	IMDG UN1263 Paint	ADG UN1263 Paint	IATA UN1263 Paint
14.3 Hazard class	3	3	3
14.4 Packing group 14.5 Environmental hazard	II	II	II
14.6 Special Provisions	163, 367 EmS-No F-E, S-E	163, 367	A3, A72, A192
14.7 Transport in Bulk According	d the IBC CODE No i	nformation available	

3YE **HAZCHEM Code:**

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP Á112), Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

New Zealand

See section 8 for national exposure control parameters

International Inventories

AICS - Australian Inventory of Chemical Substances
NZIOC - New Zealand Inventory of Chemicals

All components are listed or exempt from listing Not all components are listed or exempt from listing

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Supplier Address

Valspar Automotive Australia Pty
Limited
Unit 11/8 Kerta Road
Kincumber, NSW 2251

DBNZ Coatings Limited
6 Killarney Lane
Hamilton 3243
New Zealand

Australia T: +64 7847 0944 F: +64 7847 0932

www.valsparautomotive.com.au

Prepared by Product Stewardship

Revision Date 10-Oct-2020

Revision note Not applicable.

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet

PAGE 10/10